

# SAFETY JOGGER

## INDUSTRIAL

FOOD

### X0600 S3

Safety shoe, designed for the food industry

Upper	Nappa Action Leather
Outsole	PU/PU
Toecap	Steel
Midsole	Steel
Lining	Cambrella
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S3 / SRC
Sample weight	0.610 gr.
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 / CM 23.5-31.0




BLK



#### OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



#### STEEL MIDSOLE

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



#### WATER RESISTANT UPPER (WRU)

Prevents penetration of water if not permanently exposed to high levels.



#### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



#### SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### STEEL TOECAP

Robust metal support to protect the feet of the wearer against falling or rolling objects.

# SAFETY JOGGER INDUSTRIAL

FOOD

## X0600 S3

### Industries:

Automotive, Catering, Cleaning, Construction, Food & beverages, Industry, Logistics

### Environments:

Dry environment, Uneven surfaces, Wet environment

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Nappa Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.0	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	18.2	≥ 15
<b>Lining</b>	<b>Cambrella</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	95.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	480	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	81.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	26.2	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	28	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.0	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
42

**SAFETY  
JOGGER**  
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

[www.pls-shop.co.uk](http://www.pls-shop.co.uk)

**PLS**

ENGINEERED  
IN EUROPE