



Heavy

OXYCLOG OB

The clog that meets all your needs

The Oxylog has a rubber outsole which ensures maximum grip on both wet and dry surfaces and is compliant with the SRA non-slip standard. The clog was specially designed for the operating room and can be sterilised at high temperatures without deformation in an autoclave (at 135°C) and is washable (90°C). The Oxylog features an anti-static insert that facilitates the dissipation of static electricity, and complies with the antistatic standard ESD.



BLK



Upper	TPE
Lining	N/A
Footbed	SJ foam footbed
Outsole	TPE
Safety standard	OB / ESD, A, E, SRA
Size range	EU 35/36-47/48 / UK 3.0/3.5-12.0/13.0 US 3.0/4.0-13.0/13.5 / CM 23.0/23.5-31.0/31.5
Sample weight	0.241 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



Autoclavable
Can be sterilized in an autoclave.

Chemically & UV sterilizeable
This shoe is chemically and UV sterilizeable.

Washable 90°C
These shoes can be washed in a washing machine at 90°C.

Waterproof materials
Waterproof materials make you capable of escorting patients into the shower in a safe and hygienic way.

SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.

Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Medical, Food & beverages, Cleaning

Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	TPE			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Lining	N/A			
	Lining: permeability to water vapor	mg/cm ² /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm ²	N/A	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	N/A	≥ 400
Outsole	TPE			
	Outsole abrasion resistance (volume loss)	mm ³	120	≤ 150
	Outsole slip resistance SRA: heel	friction	0.41	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	90	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.