

SAFETY JOGGER

PROFESSIONAL

Heavy

OXYVA OB

Unmatched comfort

Upper	Expanded EVA
Lining	N/A
Footbed	Comfort Footbed
Outsole	EVA
Safety standard	OB / ESD, A, E, SRC
Size range	EU 41-45/46 / UK 7.5-10.5/11.0 US 8.0-11.5/12.0 / CM 26.5-29.5/30.0
Sample weight	0.200 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



BLK



EBL



EGN



FUX



LIC



NAV



VHT

Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.



Washable 30°C

These shoes can be washed in a washing machine at 30°C.




Waterproof materials

Waterproof materials make you capable of escorting patients into the shower in a safe and hygienic way.

Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

PLS

ENGINEERED
IN EUROPE

www.pls-shop.co.uk

Industries:

Medical, Catering, Cleaning, Food & beverages

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Expanded EVA			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Lining	N/A			
	Lining: permeability to water vapor	mg/cm ² /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm ²	N/A	≥ 20
Footbed	Comfort Footbed			
	Footbed: abrasion resistance	cycles	N/A	≥ 400
Outsole	EVA			
	Outsole abrasion resistance (volume loss)	mm ³	130	≤ 150
	Outsole slip resistance SRA: heel	friction	0.33	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	112	0.1 - 1000
	ESD value	MegaOhm	6.1	0.1 - 100
	Heel energy absorption	J	37.0	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.